



Universal tool for screwed wheel bearing assembly with 3 bolts, 7 pcs

Article No.: 440.0660

EAN: 4042146753132

Promotional price: €720.50 *

Description





- for the disassembly of screwed wheel bearings with 3 bolts at the front and rear axle
- correct disassembly directly on the vehicle
- max. load 22 t
- using both sides of the pressure feet ensures easy and quick adjustment at axle joint
- adjustability ensures use on all market available screwed and compact wheel bearings
- can be used with hydraulic cylinders or mechanical spindles
- minimum work time
- secure and easy to use
- can be used alongside 440.0074
- special tool steel

Recommended hydraulic cylinder: 16 t (440.0005) and 22 t (440.0010)

Properties

Application range:	Opel , Saab
Material1:	special tool steel
Packaging contents:	1
Packaging height, mm:	110
Packaging length, mm:	283
Packaging width, mm:	251
Parts in the set:	7
Weight [g]:	6840
max. Load kg:	22000

Consists of

Article No.	Quantity		Article	RRP: (ex. VAT)
440.0501	2 x		Locking screw M14	€66.61 *
440.0631	1 x		Traverse	€295.50 *
440.0633	1 x		Disassembly - pressure foot set for bolted wheel bearing units with...	€1,049.21 *
440.0636	2 x		Guide nut	€111.04 *