

ALUTORQUE precision torque wrench

Article No.: 516.5034

EAN: 4042146546086

Promotional price: €911.50 *

Description

- release accuracy:
- use is almost all industrial production areas
- with robust mechanism
- simple operation - fast and secure torque tightening
- simple and/or double square for controlled fastening in clockwise and counter clockwise directions
- double-scale Nm and lbf-ft and/or lbf-in division for precise adjustment
- an audible and palpable signal when the desired torque value is achieved
- secure locking possibility
- ergonomic and hand-friendly handle
- light, robust and very workshop friendly
- long service-life and high holding times
- highest precision and reliability even under tough long-term use
- setting the torque by using the captive crank lever mechanism in the handle
- comfortable setting through shapely, captive adjustment knob on the end of the handle
- extendible to reduces the workload of the user
- extremely low wear through force reductions through lever mechanism
- square drive adaptor to DIN 3120 / ISO 1174 with ball lock
- individually marked with serial number - unique product identification
- including calibration declaration of conformity according to DIN EN ISO 6789:2017(E) - traceable to national standards

Properties

Actuation accuracy:	+/-3%
Construction:	one-armed lever
Coverage in Lbf-ft:	18-90
Coverage in NM:	25-120
Division Nm:	5
Division lbf-ft:	5
Drive in inch:	1/2"
Length moment arm Lk in mm:	374
No returns allowed:	Yes
Norm:	DIN 3120, ISO 1174, DIN EN ISO 6789-1:2017(E)
Packaging height, mm:	70
Packaging length, mm:	650
Packaging width, mm:	120
Part length L2 in mm:	475
Quick release system:	yes
Ratchet function:	no
Square drive variant:	single square
Total length L1 in mm:	462
Weight [g]:	1500
height H:	30

