



## Automatic welder's protective helmet, Steel design

**Article No.:** 310.0195

**EAN:** 4042146829691

**Promotional price:** €54.50 \*

### Description

- turns fully automatically from bright after dark as soon as the light arch is ignited
  - due to high quality solar cells battery replacement is no longer require
  - equipped with a sensitivity and delaying switch for switching between dark and light to prevent welders blindness when welding at high amp capacity
  - quick switching is possible when changing from seam to spot welding
  - selection switch for reaction time
  - robust multi positional head band
  - complete neck protection
  - face protection to EN 175 / eye protection to EN379
- 1/1/1/2

### Properties

|                              |                                   |
|------------------------------|-----------------------------------|
| <b>Cassette size:</b>        | 100 x 90 x 10 mm                  |
| <b>Colour selection 1:</b>   | variable adjustment from DIN 9-13 |
| <b>Colour selection 2:</b>   | standard light adjustment DIN 4   |
| <b>Packaging contents:</b>   | 1                                 |
| <b>Packaging height, mm:</b> | 236                               |
| <b>Packaging length, mm:</b> | 330                               |
| <b>Packaging width, mm:</b>  | 235                               |
| <b>Power requirement:</b>    | litium battery + solar cells      |
| <b>Storage temperature:</b>  | -20° up tp +70°C                  |
| <b>Switching timed 1:</b>    | 1/25,000 s                        |
| <b>Switching timed 3:</b>    | 0.2 - 0.8 s delay (adjustable)    |
| <b>Total length L in mm:</b> | 295                               |
| <b>UV/IR protection:</b>     | according to EN169 / to DIN 16    |
| <b>Weight [g]:</b>           | 480                               |
| <b>Width B:</b>              | 200                               |
| <b>Window:</b>               | 100 x 50 mm                       |
| <b>Working temperature:</b>  | -5° to +55°C                      |
| <b>height H:</b>             | 220                               |



