



efuturo charging cable straight, end open to Type 2 plug for connection to a wallbox, 3-phase, up to 11 kW, 16 A, 400 V, Mode 3, 5 metres

Article No.: 117.7235
EAN: 4042146864791
Promotional price: €197.50 *

Description

- connection cable from the charging station to the vehicle
- for electric and hybrid vehicles
- end open – Type 2 (IEC 62196-2)
- up to 11 kW charging capacity
- 16 A (three-phase)
- 400 V
- mode 3
- 5 metres cable length
- with overheating protection
- TÜV approved, CE and RoHS certified

With this Mode 3 quality cable you can very rapidly, safely and reliably charge your electric or hybrid vehicle. The integrated overheating protection interrupts the electrical supply in the event of very high heat development and in this way prevents damage to the vehicle battery or the charging station. With a charging capacity of up to 11 kW and a cable length of 5 metres, this cable is ideally suited for charging at home at your own wallbox. Thanks to the ergonomically designed plug and the high-quality and durable cable, this charging cable is a reliable partner for charging your electric or hybrid vehicle. The charging plug can be locked on the vehicle. Just lock your car to do this. The plug is then firmly attached to the car and you can relax while you leave the car during the charging process.

Properties

Amperage:	max. 16 Ampere (three-phase)
Cable color:	black
Cable cross section mm²:	5* 2.5 mm ² + 1* 0.5 mm ²
Cable form:	straight
Certification:	CE, RoHS
Charging cable length:	5
Charging capacity:	up to 11 kW
Communication:	(IEC 62196-2): Mode 3
Coupling cycles:	up to 10,000
Frequency:	50
Mode:	3
Model:	efuturo charging cable straight, end open to Type 2 plug for connection to a wallbox, 3-phase, up to 11 kW, 32 A, 400 V, Mode 3, 5 metres
Packaging height, mm:	85
Packaging length, mm:	411
Packaging width, mm:	384
Plug at charging station end:	Open end for connection to wallbox
Plug at vehicle end:	Type 2
Power plug:	Loose cables /screw terminals (04)
Protection class:	IP 54 (with protective cap)
Voltage:	400 V AC
Voltage plug:	400
Working temperature:	- 25° up to + 55°C

