

## Synchronous carburettor test device with 4 synchronous clocks, 28 pcs

Article No.: 150.3600

EAN: 4042146610930

RRP: €689.93 \*



## Description

- for synchronous measurement on 2 – 4 carburetors with vacuum connection to the carburettor
- after adjustment and inspection of the valve clearances the carburetors should be synchronised
- universal usage
- unit for vacuum measurement: 0-70 cmHg / in0-30 inHg
- generally necessary after a major inspection
- optimum results for mechanical function-free engines
- must be used with running engine
- pressure gauges are fitted on the plate
- in durable plastic storage case







**Application range / for:** Multi-cylinder engines require synchronous opening of the throttle valve. Through tolerances in the intake system, adjustment of the throttle valve stop is not sufficient. Dynamic adjustment is required here. Through synchronisation, the same vacuum is reached before the carburetors. A dial is required for each carburettor for synchronisation. Adjustment of the individual compressors is done via the adjustment mechanisms.

## Properties

<b>Packaging contents:</b>	1
<b>Packaging height, mm:</b>	98
<b>Packaging length, mm:</b>	440
<b>Packaging width, mm:</b>	260
<b>Parts in the set:</b>	28
<b>Weight [g]:</b>	3000



**Consists of**

Article No.	Quantity		Article	RRP: (ex. VAT)
150.3601	4 x		Pressure gauge Ø 92 mm	€145.73 *
150.3602	4 x		Rubber house 8 x 5 x 750 mm	€12.28 *
150.3603	4 x		Hose clamp with replacement washer	€24.50 *
150.3604	4 x		Connection piece 53 mm, M6 x 0.75 mm	€20.73 *
150.3605	4 x		Connection piece 60 mm, M6 x 1.0 mm	€21.67 *
150.3606	4 x		Extension 3.9 x 52 mm	€45.16 *
150.3607	4 x		Extension 3.9 x 122 mm	€50.79 *