

3/8" mini torque wrench with protective insulation and reversible ratchet head, 5-25Nm

Article No.: 117.1184

EAN: 4042146541494

Promotional price: €577.90 *



Description

- insulated handle to IEC 60900
- for working environment of voltages AC 1000 V and DC 1500 V
- release accuracy:
- precise reading accuracy for a minimum 5,000 tightening cycles
- for controlled fastening in a clockwise direction
- can untighten without any torque restraint thanks to the anticlockwise latch
- an audible and palpable signal when the desired torque value is achieved
- exact gearing 30 teeth ratchet mechanism
- ergonomic designed handle provides secure transmission of the torque
- square drive adaptor to DIN 3120 / ISO 1174 with ball lock
- individually marked with serial number - unique product identification
- including calibration declaration of conformity according to DIN EN ISO 6789:2017(E) - traceable to national standards

Properties

Handle:	dip insulated handle
Diameter D:	40.0
Packaging width, mm:	111
Packaging height, mm:	50
Weight [g]:	440
Actuation accuracy:	+/-4%
Function attribute 1:	reversible
Norm:	DIN 3120, ISO 1174, DIN EN ISO 6789-1:2017, IEC 60900
Tooth:	30
Coverage in NM:	5-25
Drive in inch:	3/8"
Height H:	42.0
Packaging contents:	1
Total length L in mm:	200.0
Tool holder torque:	ratchet
Construction:	one-armed lever
Readout:	scale
Insulated:	insulated handle to DIN EN 609000
Test certificate:	1000V
Packaging length, mm:	256

