



Torque wrench with protective insulation and reversible ratchet head

Article No.: 117.1301

EAN: 4042146301548

Promotional price: €819.00 *

Description

- insulated handle to IEC 60900
- for working environment of voltages AC 1000 V and DC 1500 V
- release accuracy:
- precise reading accuracy for a minimum 5.000 tightening cycles
- for controlled fastening in a clockwise direction
- can untighten without any torque restraint thanks to the anticlockwise latch
- scale in Nm divisions for precise adjustment
- large vision panel for precise adjustment
- an audible and palpable signal when the desired torque value is achieved
- exact gearing 30 teeth ratchet mechanism
- torque setting is quick and easy using the locking knob in the handle end
- square drive adaptor to DIN 3120 / ISO 1174 with ball lock
- individually marked with serial number - unique product identification
- including calibration declaration of conformity according to DIN EN ISO 6789:2017(E) - traceable to national standards

Properties

Actuation accuracy:	+/-4%
Construction:	one-armed lever
Coverage in NM:	5-25
Drive in inch:	1/2"
Function attribute 1:	reversible
Handle:	dip insulated handle
Insulated:	insulated handle to DIN EN 609000
No returns allowed:	Yes
Norm:	DIN 3120, ISO 1174, DIN EN ISO 6789-1:2017, IEC 60900
Packaging contents:	1
Packaging height, mm:	50
Packaging length, mm:	305
Packaging width, mm:	105
Readout:	scale
Test certificate:	1000V
Tool holder torque:	ratchet
Tooth:	30
Total length L in mm:	280.0
Weight [g]:	930
height H:	61.0

