



## Mini torque wrench with protective insulation and reversible ratchet head

**Article No.:** 117.1402

**EAN:** 4042146306949

**Promotional price:** €704.50 \*

### Description

- insulated handle to IEC 60900
- for working environment of voltages AC 1000 V and DC 1500 V
- release accuracy:
- precise reading accuracy for a minimum 5.000 tightening cycles
- for controlled fastening in a clockwise direction
- can untighten without any torque restraint thanks to the anticlockwise latch
- an audible and palpable signal when the desired torque value is achieved
- exact gearing 30 teeth ratchet mechanism
- ergonomic designed handle provides secure transmission of the torque
- square drive adaptor to DIN 3120 / ISO 1174 with ball lock
- individually marked with serial number - unique product identification
- including calibration declaration of conformity according to DIN EN ISO 6789:2017(E) - traceable to national standards

### Properties

<b>Actuation accuracy:</b>	+/-4%
<b>Construction:</b>	one-armed lever
<b>Coverage in NM:</b>	5-25
<b>Diameter D:</b>	40.0
<b>Drive in inch:</b>	1/4"
<b>Function attribute 1:</b>	reversible
<b>Handle:</b>	dip insulated handle
<b>Insulated:</b>	insulated handle to DIN EN 609000
<b>No returns allowed:</b>	Yes
<b>Norm:</b>	DIN 3120, ISO 1174, IEC 60900, DIN EN ISO 6789-1:2017(E)
<b>Packaging contents:</b>	1
<b>Packaging height, mm:</b>	50
<b>Packaging length, mm:</b>	305
<b>Packaging width, mm:</b>	105
<b>Readout:</b>	scale
<b>Test certificate:</b>	1000V
<b>Tool holder torque:</b>	ratchet
<b>Tooth:</b>	30
<b>Total length L in mm:</b>	200.0
<b>Weight [g]:</b>	420
<b>height H:</b>	41.0

