



ESD Dial indicating torque screwdriver with a drag indicator

Article No.: 516.3260

EAN: 4042146285312

Promotional price: €471.00 *

Description

- display accuracy:
- precise reading accuracy for a minimum 5.000 tightening cycles
- for controlled display in a clockwise and counter clockwise direction
- torque screwdriver with a helical pressure spring
- ergonomic designed handle provides secure transmission of the torque
- hexagon socket holder in accordance with DIN 3126 - E6,3
- electrostatically protect
- lightweight construction due to the aluminium handle
- individually marked with serial number - unique product identification
- including calibration declaration of conformity according to DIN EN ISO 6789:2017(E) - traceable to national standards

Properties

Actuation accuracy:	+/-6%
Construction:	screwdriver
Diameter D1:	48.0
Diameter D2:	12.0
Division cNm:	2.0
Function attribute 1:	electro static discharge ESD
Hexagon drive in inches:	1/4
Hexagon drive in mm:	6,3
Measuring range cNm:	20 - 100
No returns allowed:	Yes
Norm:	DIN 3126 - E 6,3, DIN EN ISO 6789-1:2017(E)
Packaging height, mm:	95
Packaging length, mm:	255
Packaging width, mm:	100
Part length L2 in mm:	130.0
Readout:	dial indicator
Tool holder torque:	bit
Total length L1 in mm:	222.0
Weight [g]:	290

