

1/4" Stubby torque wrench, 3-15Nm

Article No.: 516.3280

EAN: 4042146284667

Promotional price: €315.00 *



Description

- actuation accuracy:
- precise reading accuracy for a minimum 5.000 tightening cycles
- for controlled fastening in a clockwise direction
- can untighten without any torque restraint thanks to the anticlockwise latch
- an audible and palpable signal when the desired torque value is achieved
- with exact gearing 72 teeth ratchet mechanism
- with ejection mechanism on the ratchet head
- ergonomic designed handle provides secure transmission of the torque
- square drive adaptor to DIN 3120 / ISO 1174 with ball lock
- individually marked with serial number - unique product identification
- including calibration declaration of conformity according to DIN EN ISO 6789:2017(E) - traceable to national standards

Properties

Actuation accuracy:	+/-3%
Backswing angle:	5°
Construction:	one-armed lever
Coverage in NM:	3-15
Diameter D:	18.0
Division Nm:	0.5
Drive in inch:	1/4"
Drive in mm:	6,3 mm
No returns allowed:	Yes
Norm:	DIN 3120, ISO 1174, DIN EN ISO 6789-1:2017(E)
Packaging height, mm:	32
Packaging length, mm:	173
Packaging width, mm:	31
Readout:	without
Tool holder torque:	ratchet
Tooth:	72
Total length L in mm:	170.0
Weight [g]:	190
Working range Nm:	3 - 15

