

Torque wrench with close gap release

Article No.: 516.3510

EAN: 4042146284391

Promotional price: €315.00 *

Description

- actuation accuracy:
- precise reading accuracy for a minimum 5.000 tightening cycles
- for controlled fastening in clockwise and counter clockwise directions
- the direction of rotation (clockwise and counter clockwise) can be changed by simply rotating the square drive piece
- four fold scale in Nm, Kg•fm, lbf•in und lbf•ft divisions for precise adjustment
- an audible and palpable signal when the desired torque value is achieved
- torque setting is easy by pulling out, adjusting and pushing in the winder in the handle
- secure locking possibility
- ergonomic handle designed for comfortable use
- square drive adaptor to DIN 3120 / ISO 1174 with ball lock
- individually marked with serial number - unique product identification
- including calibration declaration of conformity according to DIN EN ISO 6789:2017(E) - traceable to national standards

Properties

Actuation accuracy:	+/-4%
Construction:	one-armed lever
Coverage in Lbf-ft:	2 - 8
Coverage in NM:	2.5-11
Division Nm:	0.5
Division lbf•ft:	0.5
Drive in inch:	3/8"
Handle:	plastic housing
No returns allowed:	Yes
Norm:	DIN 3120, ISO 1174, DIN EN ISO 6789-1:2017(E)
Packaging height, mm:	37
Packaging length, mm:	295
Packaging width, mm:	37
Readout:	scale
Tool holder torque:	ratchet
Total length L in mm:	300.0
Weight [g]:	560



