

Air condition leak detector

Article No.: 550.1192

EAN: 4042146604748

RRP: €186.44 *



Description

- ideal for locating leaks in air conditioning pipes
- detects cooling agent concentration in the surrounding air
- reacts to R134a, R12, R11, R500, R503, R22, R123, R124, R502, R404a, R125, AZ-50, HP62 and MP39
- no cross-sensitivity in the presence of carrier gas and air movement
- with flexible stainless steel tube neck (360 mm) for places that are hard to access
- visual and aural signal upon detection of a leak
- adjustable sensitivity
- leak detection rate up to 5 g/year
- approximately 10 seconds waiting time
- service life of the sensor is approximately 50 hours
- impact proof housing
- includes 2 x C LR14 batteries
- includes replacement sensor

Properties

Accessories:	with batteries
Application in general:	automobile
Battery composition:	Alkali-Mangan (Alkaline)
Battery included:	Yes
Battery rechargeable:	No
Battery type:	LR14 (Typ C)
Height in mm:	65.0
Lithium battery included:	No
No returns allowed:	Yes
Number of batteries required:	2
Packaging contents:	1
Packaging height, mm:	75
Packaging length, mm:	345
Packaging width, mm:	359
Power requirement:	2 x LR14
Replacement sensor:	550.1194
Total length mm:	229
Voltage battery:	1,5
Weight [g]:	560
Weight battery [kg]:	0.07
Weight class battery:	class 05 (51 - 150g)
Width in mm:	65

