

Universal 3 arm puller

Article No.: 630.0101

EAN: 4042146303566

Promotional price: €107.50 *

Description

- uniform load distribution and centered tightening
- through reversing the arms internal and external applications are possible
- hydraulic spindles available for thread G1/2"
- excellent power transfer
- special tool steel

Properties

| | |
|---------------------------------|--------------------------------------|
| Arm tip depth E: | 13 |
| Arm total depth F: | 25 |
| Arm width G: | 20 |
| External hexagon drive in mm: | 17 |
| Fast adjustment: | no |
| Function attribute 1: | reversible, external+internal puller |
| Height of arm tip D: | 3 |
| Material1: | special tool steel |
| Max. torque Nm: | 90 |
| Number of arms: | with 3 arms |
| Packaging contents: | 1 |
| Packaging height, mm: | 132 |
| Packaging length, mm: | 189 |
| Packaging width, mm: | 152 |
| Span width external puller C: | 70-140 |
| Span width from [mm]: | 20 |
| Span width to [mm]: | 90 |
| Weight [g]: | 1300 |
| jaw depth B in mm: | 100 |
| max. KN: | 55,0 |
| max. Nm: | 90 |
| max. t: | 5,5 |
| maximum clamping width A in mm: | 20-90 |
| spindle size mm: | M14x1,5 x 130 |

