

12V / 24V □□□□□□□□□□□□□□□□

□□□□ 550.1649

EAN □ 4042146753699



□□

- □□□ 12V □□ (□□, □□, □□□, MF-, VRLA-, EFB-, AGM□, AGM□□ □ □□□□□)
- □□□□, □□□□
- □□□□□□□□□□
- □□□□□□□□□□□□□□□□□□□□
- □□□□□□□□□□□□□□□□□□□□
- □□□□□□, □□□□, □□□□, □□□□ □□
- □□□□□□, □□□□□□□□, □□□□□□
- □□□□□□, □□□□□□□□□□□□
- □□□□□□□□□□□□□□□□□□□□
- □□□□□□□□□□□□□□□□□□□□
- □□□□□□□□□□□□□□□□□□□□
- □□□□□□□□□□□□□□□□□□□□
- □□□□□□□□□□□□□□□□□□□□
- 3 m □□□□□□□□□□
- □□3□□□□□□, □□□□□□□□□□
- □□□□□□□□

□□

□□□□□□: □□ 12 V □□□□□□
 □□□□: 1
 □□□□ mm: 294
 □□□□ mm: 372
 □□□□ mm: 95
 □□□ CA / MCA: 40-2.000 CCA
 □□□ CCA: 40-2.000 CCA
 □□□ DIN: 40-2.000 CCA
 □□□ EN: 40-2.000 CCA
 □□□ IEC: 40-2.000 CCA
 □□□ JIS#: 40-2.000 CCA
 □□□ SAE: 40-2.000 CCA
 □□□□: 0°C □ +55°C
 □□: □□
 □□□□□□□: 550.1647
 □□□□1: +/- 0,5 Megaohm
 □□□□: 9-36 V
 □□ g: 750
 □□: 9-36 V
 □□: 100



□□					□□□□□□ □□□□□□			
□□□	□□	□□						
550.1647	1 x		□□□□ 550,1646	□□□□□□□□				